

## MODLIGHT ILLUMIX CLASSIC LINE

EXCELLENT LIGHTING FOR ANY JOB

The LED machine light Illumix Classic Line has an M12 port and displays its strengths in harsh, industrial environments:

It is robust and provides perfect illumination in daylight quality. The compact, alluminium design allows this product to be used in small spaces, so it can be mounted in almost any machine or system.

- Protected IP67 – suitable for use in environments with coolants and lubricants, flying sparks or shavings
- Extremely high daylight quality lighting (105 lm/W)
- Energy-saving LED technology – maintenance-free and durable
- Rotatable mounting brackets
- Fast and secure mounting



	Modlight Illumix Classic Line 6 W	Modlight Illumix Classic Line 12 W	Modlight Illumix Classic Line 18 W	Modlight Illumix Classic Line 24 W
<b>Order data</b>	<b>Item no.</b>	<b>Item no.</b>	<b>Item no.</b>	<b>Item no.</b>
Connection M12 Male	4000-75801-1415006	4000-75801-1415012	4000-75801-1415018	4000-75801-1415024
Connection M12 Male/Female	4000-75901-1415006	4000-75901-1415012	4000-75901-1415018	4000-75901-1415024
<b>Technical Data</b>				
Dimensions (HxWxD)	37 x 40 x 235 mm	37 x 40 x 410 mm	37 x 40 x 585 mm	37 x 40 x 760 mm
Power and rated voltage	6 W/24 V DC	12 W/24 V DC	18 W/24 V DC	24 W/24 V DC
Luminaire light current	630 lm	1260 lm	1890 lm	2520 lm
<b>Accessories</b>				
M12 cordset	Female, 4-pin, depending on cable no. (xxx) and length (yyyy) 7000-12221-xxxyyyy			
	Male/Female, 4-pin, depending on cable no. (xxx) and length (yyyy) 7000-40021-xxxyyyy			

## MODLIGHT ILLUMIX SLIM LINE

EXCELLENT LIGHTING FOR ANY JOB

The LED machine light Modlight Illumix Slim Line has an M8 port and provides perfect daylight quality.

The compact design allows this product to be used in small spaces so it can be perfectly mounted in almost any machine or system.



- Extremely high daylight quality lighting (105 lm/W)
- Energy-saving LED technology – maintenance-free and durable
- Protected IP54 – for use in the field of industrial and plant engineering
- Rotatable mounting brackets
- Fast and secure mounting



	Modlight Illumix Slim Line 4 W	Modlight Illumix Slim Line 8 W	Modlight Illumix Slim Line 16 W	Modlight Illumix Slim Line 24 W	Modlight Illumix Slim Line 32 W
<b>Order data</b>	<b>Item no.</b>	<b>Item no.</b>	<b>Item no.</b>	<b>Item no.</b>	<b>Item no.</b>
Connection M8 Male	4000-75800-1715004	4000-75800-1715008	4000-75800-1715016	4000-75800-1715024	4000-75800-1715032
Connection M8 Male/Female	4000-75900-1715004	4000-75900-1715008	4000-75900-1715016	4000-75900-1715024	4000-75900-1715032
<b>Technical Data</b>					
Dimensions (HxWxD)	34 x 24 x 218 mm	34 x 24 x 358 mm	34 x 24 x 638 mm	34 x 24 x 918 mm	34 x 24 x 1198 mm
Power and rated voltage	4 W/24 V DC	8 W/24 V DC	16 W/24 V DC	24 W/24 V DC	32 W/24 V DC
Luminaire light current	420 lm	840 lm	1680 lm	2520 lm	3360 lm
<b>Accessories</b>					
M8 cordset	Female, 4-pin, depending on cable no. (xxx) and length (yyyy) 7000-08061-xxxxyyyy				
	Male/Female, 4-pin, depending on cable no. (xxx) and length (yyyy) 7000-88011-xxxxyyyy				